

SPEC DATA SHEET



The barrier septum configuration of Vivid BSC-25 offers the benefits of both sound absorbers and noise barriers. Curtain panels are constructed with grommets across the top and hook and loop Velcro fasteners along the vertical edges. Available in rolls, standard panels sizes or custom panels. Add some color to your manufacturing and outdoor spaces with Vivid.

FEATURES:

- Excellent acoustical performance
- · Custom sizing
- Easy to install
- Durable, tear and abrasion-resistant
- Great UV and mildew resistance
- Highly water repellent
- Dimensionally stable; will not sag or stretch over time

INDOOR/OUTDOOR APPLICATIONS:

- Free-hanging acoustic curtains in acoustical curtain enclosures
- Free-hanging noise barrier/sound absorber composite wall
- Divider partition between noise sources
- Line walls or ceiling of a mechanical room or building to reduce noise inside and outside of the room or building





SPECIFICATIONS:

Visit www.soundseal.com or call 1.800.569.1294









www.soundseal.com in Y in 6









SIZING

- Rolls are available 48" W x 25' L, bound or unbound
- Standard panel size 48" x 96"
- Custom sizes available

FINISHES

- Exterior grade covering stitched with TENERA® thread
- 12 colors available

THICKNESS/SUBSTRATES

- Standard thickness: 2" fiberglass (pre-sewn)
- 1# per square foot mass-loaded vinyl
- Total weight of product: 1.5# per square foot

MOUNTING OPTIONS

- Stainless steel grommets
- Velcro seals

FIRE RATING

- Class A Flammability Rated per ASTM E- 84
- Flame Spread: 25
- Smoke density: 350

ACOUSTICAL PERFORMANCE

1/3 Octave Sound Absorption Coefficients at the Octave Band Frequencies										
Frequency (Hz)	125	250	500	1K	2K	4K	NRC			
2" Thickness	0.16	0.47	0.44	0.87	0.56	0.30	0.60			

Type A Mounting (flat)

1/3 Octave Sound Blocking Coefficients at the Octave Band Frequencies									
Frequency (Hz)	125	250	500	1K	2K	4K	STC		
2" Thickness	17	17	20	31	48	55	27		